



PO Box 14 • Somerset, MA 02726
 orders 1-800-2-BUY-DYE
 technical support 508-676-3838
 fax 508-676-3980
 e-mail • promail@prochemical.com
www.prochemical.com

Material Safety Data Sheet

PRO QuickFix

1. Product Identification

Synonyms: Water Glass; Soluble Glass; Silicate of Soda; Egg Preserver CAS No.: Not applicable to mixtures.

Molecular Weight: Not applicable to mixtures.

Chemical Formula: $\text{Na}_{20}(\text{SiO}_2)_x \cdot (\text{H}_2\text{O})_x$

Effective Date 11/12/03 * * * * * Supercedes 02/23/01

CHEMTREC: 1-800-424-9300

2. Composition/Information on Ingredients

<u>Ingredient</u>	<u>CAS NO.</u>	<u>Percent</u>	<u>Hazardous</u>
Sodium Silicate	1344-09-8	35-40%	Yes
Water	7732-18-5	60-65%	No

3. Hazards Identification

Emergency Overview

WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES SEVERE IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT.

Health Rating: 1 - Slight

Flammability Rating: 0 - None

Reactivity Rating: 0 - None

Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES; LAB COAT

Storage Color Code: Orange (General Storage) -----

Potential Health Effects

Diluted solutions of sodium silicate are strong alkaline irritants. The solid sodium silicate is corrosive. Exposure to alkaline corrosives may result in severe burns depending on the concentration and duration of exposure. Sodium silicate is a type of amorphous silica and does not cause pulmonary silicosis.

Inhalation:

A strong alkaline irritant. Inhalation can cause severe irritation of mucous membranes and upper respiratory tract. Symptoms may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. High concentrations may cause lung damage.

Ingestion:

A strong alkaline irritant. Causes irritation to the gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhea. Solid sodium silicate: Alkaline corrosive ingestion may produce burns to the lips, tongue, oral mucosa, upper airway, esophagus and occasionally stomach.

Skin Contact:

A strong alkaline irritant. Causes severe irritation. Symptoms include redness, itching and pain. Dries to form a glass film which can cut skin. Solid sodium silicate: Dermal contact with alkaline corrosives may produce pain, redness, severe irritation or full thickness burns.

Eye Contact:

A strong alkaline irritant. Alkaline eye exposures produce severe irritation with effects similar to those of dilute caustics. Inflammation or burns with possible damage to the eye tissues can occur together with tearing and considerable pain.

Chronic Exposure:

No information found.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or impaired respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Not considered to be a fire hazard.

Explosion:

Not considered to be an explosion hazard.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Caution! Floor and other surfaces may be slippery. Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Contain and recover liquid when possible. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer!

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Amorphous Silica, including natural diatomaceous earth:

OSHA Pennissible Exposure Limit (PEL):

(80 mg/m³) / (%SiO₂) (TW A).

ACGIH Threshold Limit Value (TL V):

10 mg/m³ (TW A) inhalable particulate;

3 mg/m³ (TW A) respirable particulate.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details. Personal

Respirators (NIOSH Approved):

If the exposure limit is exceeded, a half-face dust/mist respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece dust/mist respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Clear to cloudy, viscous liquid.

Odor:

Odorless.

Solubility:

Complete (100%)

Specific Gravity:

1.3 - 1.5

pH:

11 - 12.5

% Volatiles by volume @ 21C (70F):

ca. 70

Boiling Point:

102C (216F)

Melting Point:

No information found.

Vapor Density (Air=1):

Not applicable.

Vapor Pressure (mm Hg):

18 @ 20C (68F)

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity**Stability:**

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

No information found.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Fluorine, mineral acids, organic acids, organic materials. May produce hydrogen gas on prolonged contact with metals. Gels when mixed with acids.

Conditions to Avoid:

Incompatibles.

11. Toxicological InformationNo LD50/LC50 information found relating to nonnal routes -----
of occupational exposure.

\Cancer Lists\

—NTP Carcinogen

IngredientKnownAnticipatedIARC Category

Sodium Silicate (1344-09-8)

No

No

None

Water (7732-18-5)

No

No

None

12. Ecological Information**Environmental Fate:** No information found.**Environmental Toxicity:** No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.

15. Other Information

NFP A Ratings: Health: 2 Flammability: 0 Reactivity: 0

Label Hazard Warning:

WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES SEVERE IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT.

Label Precautions:

- Avoid contact with eyes, skin and clothing.
- Wash thoroughly after handling.
- Avoid breathing vapor or mist.
- Keep container closed.
- Use only with adequate ventilation.

Label First Aid:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer: *****

The manufacturer provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. THE MANUFACTURER MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, THE MANUFACTURER WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.
